



ZZ 1560

Global[®] ZZ 1560 Series - High speed zig-zag machines

TECHNICAL SPECIFICATIONS

Machine speed*
up to 5000 spm

Stitch type
304

Number of needles
1

Feed type
drop feed

Zig-zag width
0-10 mm max.

Stitch length
max. 5 mm

Hook type
1565 standard hook
1566 / 1568 large hook

Needle type
134 R or 135x17

Presser foot lift
12 mm

Extra option on ZZ 1568:
2 needle equipment. Needle distance 3, 4 & 5 mm.
Cordingset 4, 5 or 7 mm.

ZZ 1560 - High speed zig-zag machines, semi automatic lubrication, built-in bobbinwinder. Sliding excenter reverse feed, pendant link feed mechanism.

ZZ 1560 AUT - Same as ZZ 1560, but equipped with automatic thread trimmer, back tack and presser foot lifter. (all electric)

MAQUINAS DE ZIG ZAG

ZZ 1560 - Máquinas de zig zag de alta velocidad, lubricación semi automática, devanador de canilla acoplado. Deslizamiento excéntrico del inversor de puntada y mecanismo de transmisión del arrastre suspendido.

ZZ 1560 AUT - La misma que ZZ 1560, pero equipada con corta-hilos automático, alza-prensatejas y remate automático. (eléctrico)

ZICK-ZACK SCHNELLNÄHER

ZZ 1560 - Hochleistungs Zick-Zack Schnellnäher mit halbautomatischer Schmierung und eingebautem Spulapparat. Umschaltung auf Rückwärtsstich durch Gelenk und Gleitexcenter.

ZZ 1560 AUT - Baugleich mit ZZ 1560, jedoch ausgestattet mit automatischem Fadenabschneider, Fußlüftung und Verriegelung. (elektrisch)

MACHINE ZIG-ZAG


ZZ 1560 - Machine zig-zag à grande vitesse, lubrification semi automatique, bobinoir incorporé. Marche arrière par excentrique, mécanisme de griffe par bielles suspendues.

ZZ 1560 AUT - Identique à la ZZ 1560, mais équipée avec coupe-fil, relevage de pied et arrêt automatiques (électromagnétique)


Global ZZ 1560 series

The ZZ 1560 series are semi-lubricated, fast running, zig-zag machines.

ZZ 1560 series are usable on a wide variety of materials. The ZZ 1560 AUT is equipped with thread trimmer, back tack and presser foot lifter (all electric).



Global ZZ 1566



Global ZZ 1565

Specifications

model		number of needles	max. stitch length mm	max. stitch width mm	presser foot lift mm	needle system	needle Nm	Nm		max. sewing speed spm*	thread trimming device	hook
								Synthetic	Cotton			
ZZ 1565	High speed 6 mm flatbed zig zag sewing machine	1	5	6	12	134 R	80-130	20/3	30/3	5500	-	Standard
ZZ 1565 AUT	Same as ZZ 1565 - but with thread trimmer, back tack and presser foot lifter (electric)	1	5	6	12	134 R	80-130	20/3	30/3	5000	•	Standard
ZZ 1566	High speed 10 mm flatbed zig-zag sewing machine	1	5	10	12	134 R	80-130	20/3	30/3	4400	-	Large
ZZ 1566 AUT	Same as ZZ 1566 - but with thread trimmer, back tack and presser foot lifter (electric)	1	5	10	12	134 R	80-130	20/3	30/3	4400	•	Large
ZZ 1568	High speed 10 mm flatbed zig-zag sewing machine for medium heavy fabric Used in the shoe industry	1	5	10	12	134-35 R	110-160	10/3	10/3	3400	-	Large
ZZ 1568 AUT	Same as ZZ 1568 - but with thread trimmer, back tack and presser foot lifter (electric) Used in the shoe industry	1	5	10	12	134-35 R	110-160	10/3	10/3	3400	•	Large

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:
 machine model
 part numbers